


STAGE PLOT 2023 (layout only)

For questions or comments, contact Jeffrey Larson at 408-984-1960 or or e-mail LARSJEFREY@aol.com



Drum input list

1. Kick (front head mic'd)

2. Snare (top head mic'd).

3. Rack tom

4. Floor tom 1 5. Floor tom 2 6. Hi-Hat

7. Ride

8. Overhead left

9. Overhead right

10. Gong

Please refer to the attached sheet for special instructions regarding sound check, monitor requirements, and front-of-house sound requirements.



RIDER/BACKLINE EQUIPMENT 2024

For questions or comments, contact Jeffrey Larson at 408-984-1960 or or e-mail LARSJEFREY@aol.com

On Fly-away gigs the PURCHASER is to provide back-line equipment, and the following are the specific equipment requirements for producing the proper on-stage sound and visual aspects of the ZEPPELIN LIVE show. Contact the band with any questions and/or approvals regarding the equipment required.

Lead Vocalist Requirements

(Lead Vocalist supplies his own cordless mic, in-ears transmitter and receiver, digital effects and on-stage submixer for mixing and balancing of effects)

- (1) Cordless mic (IF HOUSE HAS A PREFERENCE)
- (1) Corded Shure SM58 or equiv (BACKUP MIC)
- (1) Straight microphone stand (no boom)
- (1) X-Frame keyboard/computer stand (for on-stage sub-mixer)

Guitar Amp/Speaker Requirements (Amplifiers and speakers for appearance ony, if availabe)

- (2) Marshall JCM 2000 100 watt or 50 watt head, or (2) Marshall JCM 900 100 watt or 50 watt head
- (2) Marshall 4x12 straight or slant cabinets w/Celestion vintage 30's, or (2) Marshall 4x12 straight or slant cabinets w/Celestion 25 watt Greenbacks
- (1) Gibson or Epiphone Les Paul guitar (for backup), sunburst finish preferred, new 9-42 guage strings
- (2) Guitar stands (A-frame type or equivalent)

Bass Guitar Amp/Speaker Requirements (Amplifiers and speakers for appearance ony)

- (1 or 2) Ampeg 810 or Acoustic 360/361 speaker enclosures w/amps, or equivalent (8x10, 2x15 or 1x18 type)
- (1) Shure SM58 or equiv. and Boom microphone stand
- (2) Guitar stand(s) (either a double guitar stand or 2 A-frame type)

Keyboard Requirements

- (1) Keyboard stand (X-frame type) to suitably support one standard size, 50-pound keyboard at sitting height
- (1) Keyboard/drum stool

If requested (due to airline restrictions):

• (1) 88-key weighted/semi-weighted digital piano/controller (CASIO, Roland or eq. digital piano, or Arturia Key-Lab88/StudioLogic Grand or equiv. weighted controller) *MUST HAVE USB MIDI OUT*

Drum Requirements (as listed, or equivalent)

Ludwig Bonham Reissue Amber Vistalite Kit, or Ludwig, DW, Tama w/Maple or Birch Shells:

- Drum Sizes: 1 each: 26" or 24" Bass Drum + 14" or 13" Tom Tom + 2 each: 6 x 14" Steel Snare Drums 1 of each size: 16" and 18" Floor Toms w/Legs
- Cymbals: Paiste 2002 or Zildjian A Cymbals, specified as follows (or equivalent of any item listed) 1 each: 24" Ride Cymbal + 3 each: 18" Crash Cymbals + 1 set of 15" (or 14") Hi-Hats
- Gong: 36" or 38" Paiste/Zildjian Gong with Stand
- Drum Hardware: 1 each: Cymbal Boom Stand + 3 each Straight Cymbal Stands
- Hi-Hat Stand w/ 3 legs + 2 Snare Stands + 1 each: Roc & Soc Hydraulic Drum Throne
- Drum Heads: For All Top Heads on Toms Two-ply Clear Evans G2 or Clear Remo Emperors
 All Bottom Heads on Toms One-ply Evans Resonator, or Clear Remo Ambassadors
- Snare heads: Top Snare Heads: Coated Evans G1 or Coated Remo Ambassador
- Bottom Snare Head: Clear Evans 300 Hazy Bottom Snare or Clear Remo Ambassadors
- Kick Drum: Batter (pedal) side: AQUARIAN SUPERKICK 2" ONLY PLEASE (24' OR 26" SIZES)

Miscellaneous Requirements

• (2) steel-caged fans for stage

NOTE

- **1. Lead Vocals** The Lead vocalist provides his own sub-mixing console and effects/switching control for his personal delays, and his own personal in-ear monitor system.
- 2. **Keyboards** The keyboardist provides his own sub-mixing console, his own Bass Preamp, and his own personal in-ear monitor system. Keyoards are to be very up-front in the mix. When playing keys, the bassist/keyboard player is playing left-hand keyboard bass patches that go thru the bass guitar rig (for more control and seperation out front).

NOTE